

### Directions for Use

The surface to be painted should be sanded with emery paper 180 and wiped clean.

Apply a coat of primer depending on the surface. For wooden surfaces, apply Primera White Solvent Primer. For mild and galvanized steel, apply Primera Red Oxide Primer. For walls, use Primera White Solvent Primer and allow it to dry for 6-8 hours.

Smoothen the surface by filling surface undulations with thin coats of putty for walls and wooden surfaces. Allow the surface to dry for 6-8 hours. Sand the surface with the emery paper 180 and wipe it clean.

Apply another coat of primer and allow it to dry for 6-8 hours. Sand the surface with the emery paper 320 and wipe it clean.

Apply 2 coats of Enamelo Synthetic Enamel by brush or spray at an interval of 8-10 hours between successive coats. Thin the paint by adding 10% mineral turpentine oil.

**Safety Precautions:** Store Enamelo Synthetic Enamel in a cool and dry place. Keep the container tightly closed when not in use. Wash the brush/equipment with water immediately after use.



GLOSSY  
FINISH



EXTRA  
SMOOTHNESS



EXCELLENT  
BRUSHABILITY



LONG-LASTING

JK Cement Ltd.  
Kamla Tower, Kanpur, UP - 208001  
Toll-free Number: 1800 203 4555  
Website: [www.jkmaxxpaints.com](http://www.jkmaxxpaints.com)  
Email Address: [consumercare@jkmaxxpaints.com](mailto:consumercare@jkmaxxpaints.com)



Free Sample. Not for Retail Sale.

CW: 2023



**JK ENAMELO**  
SYNTHETIC ENAMEL





Oxford Blue



Leaf Brown



Royal Ivory



Golden Yellow



Ad Grey



Golden Brown



Sandstone



Mid Buff



Phirozi



Bus Green



Smoke Grey




Mint Green



Wild Purple



Deep Orange



Truck Brown



P O Red



Brown



Signal Red

