

SURFACE PREPARATION

The surface should be dry, clean and free from dirt, grease, algal and fungal growth. New plastered surfaces should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of cement / sand mix as per directions.



PACKING

Available in 20 Ltr & 1 Ltr container packing.



FINISH



TECHNICAL SPECIFICATION

Supply & Apply of CEMENTIZIO Acrylic Synthetic Plaster over prepared surface in one coat besides primer / sealer should be given on clean wall. Thereafter a coat of CEMENTIZIO should be applied with trowel. Apply a top coat of TC-100 A (Acrylic Top Coat) after 24 hours of complete drying for extra protection & gloss.



JK MAJESTA Artisté **Crete**

Cementizio



JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001

Toll-free Number: 1800 203 4555 | Website: www.jkmaxxpaints.com

Email Address: consumercare@jkmaxxpaints.com



JK MAJESTA
Artiste^{Crete}

CEMENTIZIO
ACRYLIC SYNTHETIC PLASTER

CEMENTIZIO provides a smooth synthetic plastered surface over the prepared plastered surface. It covers hairline cracks and takes on normal thermal expansions and contractions of the surface effectively. It builds to a very durable exterior and interior finish.




COMPOSITION

It is based on high performance Acrylic Resin with silicone, micro minerals, inorganic pigments, ceramics, quartz, siliceous minerals, special biocides, fungicides, algacides, surfactants etc.




COVERING CAPACITY

Approx. 6-7 sq. ft./ kg. per coat depending on the texture and porosity of the surface.



THICKNESS

0.8 -1.0 mm depending on the texture and porosity of the surface.



TECHNICAL DATA

PRODUCT BENEFITS/FEATURES



Starry Smooth Plaster



Covers Hairline Cracks



Durable Interior and Exterior finish



Algae & Fungus Resistance



Value for Money

APPLICATION PROCEDURE

- Apply one coat of JK Primera on the surface to be painted.
- After complete drying of the sealer applied surface (min. 2 hours) apply CEMENTIZIO with stainless steel trowel. Spread the material uniformly over the surface & gently smoothen it with special stainless steel trowel to give smooth plastered finish.
- After 24 hours drying, apply one coat of TC-100 A (ACRYLIC TOP COAT) over the surface.

