

PRECAUTION



Avoid application in temperature over 40°C and below 5°C and in strong winds. Wash all equipments with water immediately after use

FINISH



JK MAJESTA Artisté **VOGUE**

Manhattan



JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001

Toll-free Number: 1800 203 4555 | Website: www.jkmaxxpaints.com

Email Address: consumercare@jkmaxxpaints.com



JK MAJESTA
Artiste VOGUE

Manhattan
DECORATIVE STONE FINISH

MANHATTAN provides the classical aged look of pitted stone, delicate to look. It covers hairline cracks. It builds to a very durable exterior and interior finish.




SURFACE PREPARATION

The surface should be dry clean and free dirt grease algal and fungal growth. New plastered surface should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of JK WallMaxx Putty as per directions.



COVERING CAPACITY

MANHATTAN cover approx. 3.5-4.5 sq. ft./ kg. per coat depending on the texture and porosity of the surface.



PACKING

Available in 20 Ltr & 1 Ltr container packing.



TECHNICAL DATA

PRODUCT BENEFITS/FEATURES



Alkali Resistant



Excellent weather and natural colour resistance



Good flexibility and adhesion



Algae & Fungus resistance



Breathes out trapped moisture



Lightfast UV resistant

APPLICATION

- Apply one coat of JK Primera Sealer of the required shade on the surface to be painted.
- After complete drying of the sealer apply manhattan with trowel. Spread the material uniformly over the surface & make the texture pattern with trowel in 2nd coat.
- Apply a top coat of TC-100 A (Acrylic Top Coat) after 24 hours of complete drying for extra protection & gloss.

