

SURFACE PREPARATION

The surface should be dry clean and free dirt grease algal and fungal growth. New plastered surface should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of JK WallMaxx Putty as per directions.



PACKING

Available in 20 Ltr & 1 Ltr container packing.



PRECAUTION



Avoid application in temperatures over 40°C and below 5°C and in strong winds. Wash all application equipment with water immediately after use.

FINISH



JK MAJESTA Artiste VOGUE

Pearl Skin



JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001
Toll-free Number: 1800 203 4555 | Website: www.jkmaxxpaints.com
Email Address: consumercare@jkmaxxpaints.com



JK MAJESTA
Artiste VOGUE

Pearl Skin

PEARL SKIN, turns drab areas into an exotic work of art. Enhancing designs are created by expert applicators in Mother of Pearl Reflective and metallic colors. The play of light reflects a spectrum of colors to accentuate the finish. A favorites of designers to make wall outstanding. Available in smoothing and dazzling shades.



APPLICATION AREA

Interior of cement sand plasters, Stucco, Concrete, Gypsum Boards, Bricks, wood. etc.



COMPOSITION


It is based on high performance Acrylic Resin with silicone, Ceramics, Quartz, Siliceous Minerals, Special Biocides, Fungicides. Algacides and Surfactants etc. It is also recommended for reviving old buildings.



COVERING CAPACITY

Pearl Skin covers approx. 16-18 sq. ft. per kg per coat depending on the porosity of the surface.

DECORIKA cover approx. 90-100 sq. ft./ Kg per coat depending on the design pattern.



DRYING TIME

Hard Dry : 8 hours.



TECHNICAL DATA

PRODUCT BENEFITS/FEATURES



Alkali resistant



Algae & Fungus resistance



Good flexibility and adhesion



Value for Money



Bridges Hairline Cracks

APPLICATION

- Apply one coat of JK Primera on the surface to be painted.
- After complete drying of the sealer apply Pearl Skin with stainless steel trowel. Spread the material uniformly over the surface & make the texture pattern with trowel.
- After 24 hours drying, apply one coat of DECORIKA of required shade by brush /roller and wash it with scraper to make light dark finish.

