## **SURFACE PREPARATION**

The surface should be dry, clean and free from dirt, grease, algal and fungal growth. New plastered surfaces should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of JK Wall Maxx Putty as per directions.



## **PACKING**

Available in 20 Ltr & 1 Ltr container packing.



## **PRECAUTION**



Avoid application in temperature over 40°C and below 5°C. Wash all equipments with water immediately after use

### **FINISH**



#### JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001
Toll-free Number: 1800 203 4555 | Website: www.jkmaxxpaints.com

Email Address: consumercare@jkmaxxpaints.com







# MAJESTA Artisté vogue

#### **SORRENTO**

CLASSICAL SILKEN VELVET INTERIOR FINISH

**SORRENTO** represents the neo classical finish to enamour the mind with dazzling pearl effects. It resembles the silken velvetused in the Palaces and Villas of the royalty during the European Renaissance period. the effects can be toned with the play of lighting.



## **TECHNICAL DATA**

## PRODUCT BENEFITS/FEATURES



Alkali resistant



Bridges Hairline Cracks



Good flexibility and adhesion



Algae and Fungus Resistance




Breathes out trapped moisture



Water Repellent

## **COMPOSITION**


It is based on high performance Acrylic Resin with silicone, micro minerals, inorganic pigments, ceramics, special pearl pigments, siliceous minerals, special biocides, fungicides, algaecides, surfactants etc.



### **COVERAGE**

SORRENTO cover approx. 90-100 sq. ft./ ltr per coat depending on the texture and porosity of the surface.

SATENATO cover approx. 100-150 sq. ft./ ltr per coat depending on the design pattern.



## **APPLICATION**

- a) Apply one coat of JK Primera of required shades on the surface to be painted.
- b) After complete drying of the primer apply Sorrento by brush/roller.
- c) After 4 hours drying, apply Satenato with designer tools (Sponge) to create designer pattern.



