


## SURFACE PREPARATION

The surface should be dry clean and free dirt grease algal and fungal growth. New plastered surface should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of JK WallMaxx Putty as per directions.



## THINNER

Can be thinned with 2-3 % potable water as per requirement.



## PACKING

Available in 20 Ltr & 1 Ltr container packing.



## PRECAUTION



Avoid application in temperatures over 40°C and below 5°C and in strong winds. Wash all application equipment with water immediately after use.

## FINISH



# JK MAJESTA Artiste VOGUE

## Stucco Veneziano



### JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001  
Toll-free Number: 1800 203 4555 | Website: [www.jkmaxxpaints.com](http://www.jkmaxxpaints.com)  
Email Address: [consumercare@jkmaxxpaints.com](mailto:consumercare@jkmaxxpaints.com)



**JK MAJESTA**  
**Artiste VOGUE**

**STUCCO VENEZIANO**  
SILK SMOOTH FINISH

**STUCCO** provides a smooth three dimensional finish to accentuate a royal aura. It is silk smooth to touch and provide an ancient painting like effect. It transforms sedate walls to a luxurious polished Italian marble look.



**APPLICATION AREA**

interior of cement sand plasters, Stucco, Concrete, Gypsum Boards, Bricks, wood. etc.




**COMPOSITION**

It is based on high performance Acrylic Resin with silicone, Ceramics, Quartz, Siliceous Minerals, Special Biocides, Fungicides, Algacides and Surfactants etc.



**COVERAGE**

Approx. 25-30 sq. ft. per kg. in 3 coats depending on the porosity of the surface.



**DRYING TIME**

Hard Dry : 8 hours.



**TECHNICAL DATA**

**PRODUCT BENEFITS/FEATURES**



Three dimensional like finish in mirror gloss effect



Good Adhesion



Algae and Fungus resistance



Light-fast UV Resistant



Prolongs the life of the structure



Bridges Hairline Cracks

**APPLICATION**

- JK Primera coat as Sealer / primer of required shade.
- Apply the 1st coat of STUCCO of required shade by the stucco trowel as smooth plaster.
- apply the 2nd coat of stucco as patches with the help of stucco trowel
- After semi drying apply the thin layer of stucco in desired pattern and buff it with stucco trowel to finish it with mirror like gloss.

