

SURFACE PREPARATION

The surface should be dry clean and free dirt grease algal and fungal growth. New plastered surface should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of JKWallMaxx Putty as per directions.



PACKING

Available in 20 Ltr & 1 Ltr container packing.



PRECAUTION



Avoid application in temperatures over 40°C and below 5°C. Wash all application equipment with water immediately after use.

FINISH



JK MAJESTA Artiste VOGUE

Velvetino

JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001
Toll-free Number: 1800 203 4555 | Website: www.jkmaxxpaints.com
Email Address: consumercare@jkmaxxpaints.com



JK MAJESTA
Artiste VOGUE

VELVETINO
METALLIC SILK EFFECT FINISH

VELVETINO provides an unusual silk effect and extraordinary beautiful luminescent metallic reflections. It is soft and delicate to touch. Gives a very elegant look to the walls. It is environment friendly and water based.



APPLICATION AREA

Interior of Cement Sand plasters, Stucco, Concrete, Gypsum Boards, Bricks, wood. etc.




COMPOSITION

It is based on high performance Acrylic Resin with silicone, metallic pigments, Siliceous Minerals, Special Biocides, Fungicides. Algaecides and Surfactants etc.



COVERING CAPACITY

Approx. 80-100 sq. ft. per Ltr in 2 coat .



DRYING TIME

Hard Dry : 8 hours.



TECHNICAL DATA

PRODUCT BENEFITS/FEATURES



Algae & Fungus Resistance



Instant Smooth Wave Like Finish



Good flexibility and adhesion



Bridges Hairline Cracks



Value for Money

APPLICATION

- JK Primera coat as Sealer / primer.
- Apply the one coat of SATENATO as base coat of required shade by the brush/roller.
- After 4 hrs drying apply one coat of VELVETINO as smooth plaster by stucco trowel.
- After 4 hrs drying apply the 2 coat of VELVETINO by stucco trowel in wave pattern.

