


SURFACE PREPARATION

The surface should be dry clean and free dirt grease algal and fungal growth. New plastered surface should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of Acro Polyplaster as per directions.



PACKING

Available in 25 Kg & 30 Kg packing.



PRECAUTION



- a) Avoid application in temperature over 40°C and below 5°C and in strong winds. Wash all equipment with water immediately after use.

JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001

Toll-free Number: 1800 203 4555 | Website: www.jkmaxpaints.com

Email Address: consumercare@jkmaxpaints.com



JK MAJESTA Artisté VOGUE

Marmo Classic



JK MAJESTA
Artiste VOGUE

Marmo Classic
ACRYLIC SYNTHETIC TEXTURE PLASTER

MARMO CLASSIC provides a smooth textured synthetic plastered surface over the prepared plastered surface. It covers hairline cracks and takes on normal thermal expansions and contractions of the surface effectively. It builds to a very durable exterior and interior finish.




COMPOSITION

It is based on high performance Acrylic Resin with silicone, micro minerals, inorganic pigments, ceramics, quartz, siliceous minerals, special biocides, fungicides, algacides, surfactants etc.



COVERAGE

- **MARMO CLASSIC BASE** cover approx. 5-6 sq. ft./ kg. per coat depending on the texture and porosity of the surface.
- **MARMO CLASSIC TOP (ANTICA)** covers approx. 150-180 sq.ft./ltr./coat.



Approx. 5 – 6 sq. ft. per coat



Approx. 150 – 180 sq. ft./ ltr. /coat

TECHNICAL DATA

PRODUCT BENEFITS/FEATURES



Algae & Fungus Resistance



Instant Smooth Wave Like Finish



Good flexibility and adhesion



Bridges Hairline Cracks



Value for Money

APPLICATION

- Apply one coat of Polyunder Sealer on the surface to be painted.
- After complete drying of the sealer apply **MARMO CLASSIC** with stainless steel trowel. Spread the material uniformly over the surface & make the texture pattern with trowel.
- After 24 hours drying, apply one coat of **ANTICA** of required shade by brush /roller and wash it with sponge to make light dark finish.
- Apply a top coat of **TC-100 A (Acrylic Top Coat)** after 24 hours of complete drying for extra protection & gloss.

