


## SURFACE PREPARATION

The surface should be dry clean and free dirt grease algal and fungal growth. New plastered surface should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of JK WallMaxx Putty as per directions.



## THINNER

Can be thinned with 3-8 % potable water as per requirement.



## PACKING

Available in 25 Kg & 30 Kg packing.



## PRECAUTION



Avoid application in temperatures over 40°C and below 5°C and in strong winds. Wash all application equipment with water immediately after use.

## FINISH

High build granular acrylic aggregate textured (semi rough starry, finish) wall coating in pigmented finish by spray gun.



# JK MAXIMO Patternz

## ACRO ROCK SPRAY



### JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001

Toll-free Number: 1800 203 4555 | Website: [www.jkmaxxpaints.com](http://www.jkmaxxpaints.com)

Email Address: [consumercare@jkmaxxpaints.com](mailto:consumercare@jkmaxxpaints.com)



# JK MAXIMO Patternz

## ACRO ROCK SPRAY HIGH BUILD GRANULAR TEXTURED WALL FINISH

ACRO ROCK SPRAY is a tinted granular textured wall finish for the protection and decoration in the exteriors and interiors.



### APPLICATION AREA

Exterior and interior of cement sand plasters, Stucco, Concrete, Gypsum Boards, Bricks, wood. etc.




### COMPOSITION

It is based on high performance Acrylic Resin with silicone, In-organic pigments. Ceramics, Quartz, Siliceous Minerals, Special Biocides, Fungicides, Algaecides and Surfactants etc. It is also recommended for reviving old buildings.



### COVERAGE

Approx. 6.5-7.5 sq. ft. per kg. depending on the porosity of the surface.



### DRYING TIME

Hard Dry : 8 hours.



## TECHNICAL DATA

### PRODUCT BENEFITS/FEATURES



Alkali resistant



Excellent  
Weather Resistance



Good flexibility  
and adhesion



Algae and  
Fungus Resistance



Breathes out  
trapped moisture



Water Repellent

### APPLICATION

- JK Primera coat as Sealer / primer
- Spray the ACRO ROCK SPRAY by spray gun to get semi rough stary finish.

