
SURFACE PREPARATION

The surface should be dry, clean and free from dirt, grease, algal and fungal growth. New plastered surfaces should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of JK WallMaxx Putty as per directions.



THINNER



PACKING

Available in 25 Kg & 30 Kg packing.



PRECAUTION



Avoid application in temperatures over 40°C and below 5°C and in strong winds. Wash all application equipments with water immediately after use.

FINISH

High build granular acrylic aggregate textured (starry finish) wall coating in pigmented finish by S.S. trowel & finished with Polystyrene trowel.




JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001

Toll-free Number: 1800 203 4555 | Website: www.jkmaxxpaints.com

Email Address: consumercare@jkmaxxpaints.com









™MAXIMO Patternz

GRAFFIATO FINE GRANULAR TEXTURED WALL FINISH

GRAFFIATO FINE is a tinted granular textured wall finish for the protection and decoration in the exteriors and interiors.



TECHNICAL DATA

PRODUCT BENEFITS/FEATURES



Alkali resistant



Excellent Weather Resistance



Good flexibility and adhesion



Algae and Fungus resistance




Breathes out trapped moisture



Water Repellent

COMPOSITION

It is based on high performance Acrylic Resin with silicone, In-organic pigments, Ceramics, Quartz, Siliceous Minerals, Special Biocides, Fungicides, Algicides and Surfactants etc. It is also recommended for reviving old buildings.



COVERAGE

Approx. 3.5 to 4.5 sq. ft./ kg. per coat depending on the texture and porosity of the surface.

DRYING TIME

Hard Dry: 8 hours.

APPLICATION

The priming coat should be of JK Primera of required shade. It can be thinned upto 50-60 % with tap water as per the porosity of surface. Spread the material of GRAFFIATO FINE uniformly over the surface and make the pattern with the help of polystyrene trowel.

