
SURFACE PREPARATION

The surface should be dry, clean and free from dirt, grease, algal and fungal growth. New plastered surfaces should be allowed to cure for at least 28 days. Surface imperfection should be removed with the use of JK WallMaxx Putty as per directions.



THINNER

Can be thinned with 3-4 % potable water as per requirement.



PRECAUTION



Avoid application in temperatures over 40°C and below 5°C and in strong winds. Wash all application equipments with water immediately after use.

PACKING

Available in 25 Kg & 30 Kg packing.



FINISH

High build granular acrylic aggregate textured (semi rough starry finish) wall coating in pigmented finish by S.S. trowel & finished with Polystyrene trowel.




JK Cement Ltd.

Kamla Tower, Kanpur, UP - 208001

Toll-free Number: 1800 203 4555 | Website: www.jkmaxxpaints.com

Email Address: consumercare@jkmaxxpaints.com









MAXIMO Patternz

Rustic Fine
TEXTURED WALL FINISH

RUSTIC REGULAR is a tinted granular textured wall finish for the protection and decoration in the exteriors and interiors.



TECHNICAL DATA

PRODUCT BENEFITS/FEATURES



Alkali resistant



Excellent Weather Resistance



Good flexibility and adhesion



Algae and Fungus resistance



Breathes out trapped moisture



Light-fast UV resistant

APPLICATION AREA

Exteriors and interior of cement sand plasters, Stucoo, Concrete, Gypsum Boards, Bricks, Wood, etc.



COVERAGE

Approx. 4 - 5 sq. ft./ kg. per coat depending on the texture and porosity of the surface.



COMPOSITION

It is based on high performance Acrylic Resin with silicone, In-organic pigments, Ceramics, Quartz, Siliceous Minerals, Special Biocides, Fungicides, Algaecides and Surfactants etc. It is also recommended for reviving old buildings.

DRYING TIME

Hard Dry : 8 hours.



APPLICATION

- a) JK Primera coat as Sealer / Primer
- b) Material application with s/s trowel & finished with polystyrene trowel.

