



## JK WIPEAZY

### Super Premium Interior Emulsion

JK WipEazy is an Interior water based Super Premium Emulsion. It is formulated with properties like Best in Class Washability, Rich Sheen, Stain Guard Technology which ensures Long Life of the finish on the walls.

## PRODUCT BENEFITS/FEATURES



Best in Class  
Washability



Rich Sheen



Long Life



Performance Warranty  
10 Years



Interior



Low-VOC

## AREAS OF APPLICATION

JK WipEazy Super Premium Interior Emulsion can be applied on Plastered Surfaces.

## PACKAGING AVAILABLE



1 L



4 L




10 L



20 L

## COVERAGE

On normal masonry surface by brush/roller/spray



**2 Coats** 120-130 sq.ft/ltr\*

\*Actual Coverage may vary from the quoted coverage due to factors such as method and condition of application, surface roughness and porosity.

## FINISH

Smooth

Sheen

## COLORS AVAILABLE

**JK WipEazy is a Top Coat**  
White, Bases : P1, M1, D1, A1



## HOW TO APPLY

### SURFACE PREPARATION

- For best results, proper surface preparation is essential.
- Newly plastered surfaces should be allowed to mature for 6-8 weeks.
- The surface to be painted should be clean, dry and free from dust, dirt, or loose particles, grease, chalking, etc.
- This should be done by washing the surface with water.
- All surfaces to be painted should be thoroughly sanded with emery paper 180 and wiped clean.
- All surface seepage or leakage should be properly repaired.
- All fungus/algae-affected areas must be treated.

### APPLICATION

- PRIMER: Apply a coat of JK Primera Interior Wall Primer and allow drying for 4-6 hours.
- PUTTY: Smoothen the surface by filling pinholes or cracks with a thin coat of JK WallMaxX Putty and allowing it to dry for 4-6 hours. Sand the surface with emery paper no. 180 and wipe it clean.

### PRIMER:

- Apply another coat of JK Primera Interior Wall Primer and allow it to dry for 4-6 hours. Sand the surface with emery paper no. 320 and wipe it clean.

### TOPCOAT:

- Dilute 1 litre of JK WipEazy Interior Emulsion with 400-500 ml of water. Apply 2-3 coats of this diluted paint with a gap of 4-6 hours between two coats.

### SHELF LIFE

- 3 years from the date of manufacturing in the original tightly closed container, away from direct sunlight and excess heat.
- Lead contents does not exceed 90 ppm.
- No Added Mercury, Arsenic and Chromium.
- Stir well and strain before use.

## JK WIPEAZY APPLICATION PROCESS

| APPLICATION                                                  | THINNER                                   | DILUTION %<br>VOLUME    | APPLICATION<br>VISCOSITY <sup>1</sup> (SEC)          | RECOATING<br>PERIOD <sup>2</sup> (HOURS) |
|--------------------------------------------------------------|-------------------------------------------|-------------------------|------------------------------------------------------|------------------------------------------|
| Surface Preparation                                          | Cleaning & Sanding with Emery Paper 180   |                         |                                                      |                                          |
| <b>Step 1</b><br>JK Primeria Interior wall primer.           | Water                                     | 100%                    | Brush/ Roller- 15- 20<br>Sec<br>Spray - 15 - 20 Sec  | 4-6 hours                                |
| <b>Step 2</b><br>JKCement WallMaxX Wall Putty.               | Water                                     | Based on<br>Requirement | NA                                                   | 4-6 hours                                |
|                                                              | Cleaning and Sanding with Emery Paper 180 |                         |                                                      |                                          |
| <b>Step 3</b><br>JK Primera Interior wall primer             | Water                                     | 100%                    | Brush/ Roller- 15- 20<br>Sec<br>Spray - 15 - 20 Sec  | 4- 6 hours                               |
|                                                              | Cleaning and Sanding with Emery Paper 320 |                         |                                                      |                                          |
| <b>Step 4</b><br>JK WipEazy Interior Emulsion-<br>First Coat | Water                                     | 40-50%                  | Brush/ Roller- 45 - 60<br>Sec<br>Spray - 45 - 60 Sec | 4-6 hours                                |
| <b>Step 5</b><br>JK WipEazy Interior Emulsion-<br>First Coat | Water                                     | 40-50%                  | Brush/ Roller- 45 - 60<br>Sec<br>Spray - 45 - 60 Sec | 4-6 hours                                |

1. As measured through a Ford cup.

2. Recoating period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

3. Some shades may require 3 or more coats for proper hiding.

## PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- In high humidity areas, use of bio-wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of paint.

## TECHNICAL DETAILS

**Drying time:** Surface dry time 30 min.

**Sheen levels:** 15-20 at 60° GH

**Flash point IS101/1987 Part 1, Sec 6:** NA

**Stability of thinned paint:** To be used within 24 hours

## SAFETY FEATURES

- Kindly refer to the MSDS for JK Primera Interior Wall Primer which gives detailed information on safety measures while handling the primer.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink, etc.
- May be harmful, if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water.
- Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- Safety Data Sheet available for professional user on request.
- No added Lead, Mercury or Chromium compounds.