



JK WOODFILL

JK WoodFill is high performance water based wood filler. It can be used for minor wood dents, scratch, hole or surface repairs. It can be used for both interior and exterior.

PRODUCT BENEFITS/FEATURES



Excellent Grain Clarity



Interior & Exterior



Available in 3 Shades

AREAS OF APPLICATION

JK WoodFill can be applied on Natural Wood, Engineered wood, Plywood, MDF/HDF.

PACKAGING AVAILABLE



500 gm



1 kg

COLORS AVAILABLE

- White
- Teak
- Walnut



HOW TO APPLY

- **SANDING:** Sand the wooden surface along the grains using sand paper no. 180, and then 320 or 400. Wipe surface to clean off loose dust particles.
- **INSULATING:** Apply 1-2 coats of JKC Wood Amore PU Insulator to insulate from oil & resin from the wood, also it reduces absorption of a paint material on Plywood & MDF area thoroughly.
- **DENT FILLING:** Apply JK WoodFill with a putty knife over the dented After drying, sand the surface with 180/220/320 emery paper and if required recoat with JK WoodFill.
- **Stain Application:** Apply JKC Wood Amore Wood stain as per required selected shade.
- **Paint Application:** Apply the Sealer/Filler and Topcoats as per recommended process.

PRECAUTIONS

- Store in a cool and dry place. Keep the container tightly closed when not in use.
- Mix well before use.
- For optimum performance, use JK WoodFill must be applied at a temperature between 20°C and 40°C and humidity not above 75%.
- Keep away from direct sun light.

TECHNICAL DETAILS

- a. **Sanding Time** : 1 - 2 hours
- b. **Recoating Time** : 2 hours
- c. **Flash Point** : Not applicable
- d. **Shelf Life** : 1 Year from date of manufacturing
(Note: Sanding and recoating time varies on temperature, humidity and thickness of application)

SAFETY FEATURES

- Kindly refer to the MSDS of JK WoodFill, which gives detailed information on safety measures while handling the paint.
- No added Lead, Mercury or Chromium compounds.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink etc.

- May be harmful, if swallowed. In case of ingestion, seek immediate medical attention.
- In case of skin irritation immediately, wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Use protective equipments like rubber / polyurethane gloves, safety goggles / glasses, face mask while handling the paint.
- Dispose in land filling. Do not dispose in any drain or water-channel.