

JK Maxx Crack Repair ACRYLIC PASTE

JK Maxx Crack Repair is a premium quality acrylic modified crack bridging paste. It provides excellent solution for bonding and crack bridging suitable for internal and external masonry surfaces.



PRODUCT BENEFITS/FEATURES



HIGH BONDING



CRACK BRIDGING
UPTO 5MM



INTERIOR &
EXTERIOR

AREAS OF APPLICATION

External and Internal plastered brick masonry wall cracks of upto 5 mm width

PACKAGING AVAILABLE //



500 g



1 kg



5 kg

COVERAGE //

On normal masonry surface by brush/roller/spray



25 - 30 running meter/kg

(for a depth of 5 mm and width of 5 mm)

*Coverage may vary based on porosity of the surface.

DIRECTIONS FOR USE HOW TO APPLY

SURFACE PREPARATION:

1. Surface should be free from dust, oil, grease and any contaminants, surface should be moistened before application of JK Maxx Crack Repair Paste
2. For best results, proper surface preparation is essential. For treatment of affected surface, existing POP or painter's putty must be removed till plaster surface is exposed.

APPLICATION:

- Hairline cracks must be widened upto 2-3 mm width & the surface should be primed with suitable JK Primer.
- Fill one coat by JK Maxx Crack Repair not exceeding 5mm, from each side of the crack.
- Press JK Maxx Crack Repair firmly into the cracks with a spatula or putty knife or trowel and level with the surface. Apply Second Coat of JK Maxx Crack Repair paste after 4-6 hours.

TECHNICAL DETAILS

Colour	:	White
Specific Gravity at 25°C	:	1.48 ± 0.02 (ASTM D : 3800 - 79)
Consistency	:	Viscous paste
Non Volatile Content, %	:	75 - 80 (ASTM D : 1010)
Tack Free Time, Minutes	:	35 - 45 (ASTM D : 2377)
Vertical Slump, mm	:	Nil (ASTM D : 2202)
Service temp. range, °C	:	-15 to + 80
Extension recovery, %	:	Min 75 (ASTM C : 736)
Freeze / thaw stability, cycles	:	Passes 5
Volume Shrinkage, %	:	20 (ASTM C : 1241)

PRECAUTIONS

- Should not be used for cracks more than 5 mm thick.
- Not for application in cracks in structural members, expansion joints and separation gaps.
- Drying time could be delayed for application below 10°C.
- Container should be closed tightly after application.

SAFETY FEATURES

- Wear suitable protective clothing, gloves, goggles and respiratory equipment during application.
- In case of contact with skin and eyes, wash with plenty of water and seek medical advice if necessary.
- If swallowed, seek medical attention immediately. Do not induce vomiting.
- Keep out of reach of children's and away from eatables.
- No added Lead, Mercury or Chromium Compounds.

Marketed by

JK Maxx Paints Limited

Kamla Tower, Kanpur, UP- 208001

Consumer Care Cell: For feedback/complaints write to the above address,

Toll-free Number : 1800 203 4555, Website : www.jkmaxxpaints.com,

E-mail Address : consumercare@jkmaxxpaints.com