



## JK TRENDZ TRU-SHYN

### Premium Interior Emulsion

JK TRENDZ TRU-SHYN INTERIOR EMULSION is a premium interior emulsion comes with Rich Sheen and offers Advanced Chromasure Tech which gives your house ultimate assurance of colour sustenance with upto 8 years warranty.

## PRODUCT BENEFITS/FEATURES



Rich Sheen



Advanced  
Chromasure Tech



Anti Fungal



8 Years Warranty



Interior



Low-VOC

## AREAS OF APPLICATION

JK Trendz Tru-Shyn Premium Interior Emulsion can be applied on plastered surfaces.

## PACKAGING AVAILABLE



1 L



4 L




10 L



20 L

## COVERAGE

On normal masonry surface by brush/roller/spray



120-130 sq.ft/ltr\* on normal masonry  
surface by brush/roller/spray

\*Actual Coverage may vary from the quoted coverage due to factors such as method and condition of application, surface roughness and porosity.

## FINISH

Smooth

Sheen

## COLORS AVAILABLE

White, Bases : P1, M1, D1, A1  
JK Trendz Tru-Shyn is a Top Coat



## HOW TO APPLY

### SURFACE PREPARATION

- For best results, proper surface preparation is essential.
- Newly plastered surfaces should be allowed to mature for 6-8 weeks.
- The surface to be painted should be clean, dry and free from dust, dirt, or loose particles, grease, chalking, etc.
- This should be done by washing the surface with water.
- All surfaces to be painted should be thoroughly sanded with emery paper 180 and wiped clean.
- All surface seepage or leakage should be properly repaired. All fungus/algae-affected areas must be treated.

## APPLICATION

### PRIMER

- Apply a coat of JK Primera Interior Wall Primer and allow drying for 4-6 hours.

### PUTTY

- Smoothen the surface by filling pinholes or cracks with a thin coat of JK WallMaxX Putty and allowing it to dry for 4-6 hours. Sand the surface with emery paper no. 180 and wipe it clean.

### PRIMER

- Apply another coat of JK Primera Interior Wall Primer and allow it to dry for 4-6 hours. Sand the surface with emery paper no. 320 and wipe it clean.

### TOPCOAT

- Dilute 1 litre of JK Trendz Tru-Shyn Premium Interior Emulsion with 400-500 ml of water. Apply 2-3 coats of this diluted paint with a gap of 4-6 hours between two coats.

### SAFETY PRECAUTIONS

- Stir the contents thoroughly and strain before use.
- Store Trendz Tru-Shyn Premium Interior Emulsion in a cool and dry place.
- Keep the container tightly closed when not in use.
- Wash the brush/equipment with water immediately after use.

### SHELF LIFE

- 3 years from the date of manufacturing in the original tightly closed container, away from direct sunlight and excess heat.

- Lead contents does not exceed 90 ppm.
- No Added Mercury, Arsenic and Chromium.
- Stir well and strain before use.

## JK TRENDZ TRU-SHYN PREMIUM APPLICATION PROCESS

APPLICATION	THINNER	DILUTION % VOLUME	APPLICATION VISCOSITY <sup>1</sup> (SEC)	RECOATING PERIOD <sup>2</sup> (HOURS)
Surface Preparation	Cleaning & Sanding with Emery Paper 180			
<b>Step 1</b> JK Primera Interior Wall Primer	Water	100%	Brush/Roller 15-20 Sec Spray 15-20 Sec	4-6 hours
<b>Step 2</b> JK Cement WallMaxX Wall Putty	Water	Based on requirement	N/A	4-6 hours
	Cleaning & Sanding with Emery Paper 180			
<b>Step 3</b> JK Primera Interior Wall Primer	Water	100%	Brush/Roller 15-20 Sec Spray 15-20 Sec	4-6 hours
	Cleaning & Sanding with Emery Paper 320			
<b>Step 4</b> JK Trendz Tru-Shyn Interior Emulsion- First Coat	Water	40-50%	Brush/ Roller- 45-60 Sec Spray - 45-60 Sec	4-6 hours
<b>Step 5</b> JK Trendz Tru-Shyn Interior Emulsion- Second Coat	Water	40-50%	Brush/ Roller- 45-60 Sec Spray - 45-60 Sec	4-6 hours

1. As measured through a Ford cup.

2. Recoating period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

3. Some shades may require 3 or more coats for proper hiding.

## PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- In high humidity areas, use of bio-wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of paint.

## TECHNICAL DETAILS

**Drying time:** Surface dry time 30 min.

**Sheen levels:** 8-10 at 60° GH

**Flash point IS101/1987 Part 1, Sec 6:** NA

**Stability of thinned paint:** To be used within 24 hours

## SAFETY FEATURES

- Kindly refer to the MSDS for JK Primera Interior Wall Primer which gives detailed information on safety measures while handling the primer.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink, etc.
- May be harmful, if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin

with soap and plenty of water. Get medical attention if irritation develops or persists.

- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- Safety Data Sheet available for professional user on request.
- No added Lead, Mercury or Chromium compounds.