

TECHNICAL DATA SHEET



JK MAJESTA TRU-SHYN

Luxury Interior Emulsion

Elevate your interiors with P.U.R.A (PU Reinforced Advanced Tech) for unmatched film strength and superior resilience. It delivers a captivating, deep Luxe Sheen that transforms walls into a surface of sheer sophistication. Experience the perfect fusion of advanced durability and lasting, opulent beauty.

PRODUCT BENEFITS/FEATURES



12 Years Warranty



Luxe Sheen



PU-RA Tech



Crack Shield Tech



Exquisite Whiteness



Interior

AREAS OF APPLICATION

JK Majesta Tru-Shyn Luxury Interior Emulsion can be applied on Plastered Surfaces.

PACKAGING AVAILABLE



1 L



4 L



10 L



20 L

COVERAGE

On normal masonry surface by brush/roller/spray



2 Coats 140-160 sq.ft/ltr*

*Actual Coverage may vary from the quoted coverage due to factors such as method and condition of application, surface roughness and porosity.

FINISH

Luxe Sheen

COLORS AVAILABLE

JK Majesta Tru-Shyn is a Top Coat

White, Bases : P1, M1, D1, A1



HOW TO APPLY

SURFACE PREPARATION

- For best results, proper surface preparation is essential.
- Newly plastered surfaces should be allowed to mature for 6-8 weeks.
- The surface to be painted should be clean, dry and free from dust, dirt, or loose particles, grease, chalking, etc.
- This should be done by washing the surface with water.
- All surfaces to be painted should be thoroughly sanded with emery paper 180 and wiped clean.
- All surface seepage or leakage should be properly repaired.
- All fungus/algae-affected areas must be treated.
- Newly plastered surfaces should be allowed to mature for 6-8 weeks.

APPLICATION

- PRIMER: Apply a coat of JK Primera Interior Wall Primer and allow drying for 4-6 hours.
- PUTTY: Smoothen the surface by filling pinholes or cracks with a thin coat of JK WallMaxX Putty and allowing it to dry for 4-6 hours. Sand the surface with emery paper no. 180 and wipe it clean.

PRIMER:

- Apply another coat of JK Primera Interior Wall Primer and allow it to dry for 4-6 hours. Sand the surface with emery paper no. 320 and wipe it clean.

TOPCOAT:

- Dilute 1 litre of JK Majesta Tru-Shyn Interior Emulsion with 400-500 ml of water. Apply 2-3 coats of this diluted paint with a gap of 4-6 hours between two coats.

SHELF LIFE

- 3 years from the date of manufacturing in the original tightly closed container, away from direct sunlight and excess heat.
- Lead contents does not exceed 90 ppm.
- No Added Mercury, Arsenic and Chromium.
- Stir well and strain before use.

JK MAJESTA TRU-SHYN APPLICATION PROCESS

APPLICATION	THINNER	DILUTION % VOLUME	APPLICATION VISCOSITY ¹ (SEC)	RECOATING PERIOD ² (HOURS)
Surface Preparation	Cleaning & Sanding with Emery Paper 180			
Step 1 JK Primera Interior wall primer.	Water	100%	Brush/ Roller- 15- 20 Sec Spray - 15 - 20 Sec	4-6 hours
Step 2 JKCement WallMaxX Wall Putty.	Water	Based on Requirement	NA	4-6 hours
	Cleaning and Sanding with Emery Paper 320			
Step 3 JK Primera Interior wall primer	Water	100%	Brush/ Roller- 15- 20 Sec Spray - 15 - 20 Sec	4- 6 hours
	Cleaning and Sanding with Emery Paper 320			
Step 4 JK Majesta Tru-Shyn Interior Emulsion- First Coat	Water	40-50%	Brush/ Roller- 45 - 60 Sec Spray - 45 - 60 Sec	4-6 hours
Step 5 JK Majesta Tru-Shyn Interior Emulsion- Second Coat	Water	40-50%	Brush/ Roller- 45 - 60 Sec Spray - 45 - 60 Sec	4-6 hours

1. As measured through a Ford cup.

2. Recoating period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

3. Some shades may require 3 or more coats for proper hiding.

PRECAUTIONS

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hours of application.
- In high humidity areas, use of bio-wash solution is recommended to remove surface fungus growth, fungal spores, mould etc. before application of paint.

TECHNICAL DETAILS

Drying time: Surface dry time 30 min.

Sheen levels: 15-25 at 60° GH

Flash point IS101/1987 Part 1, Sec 6: NA

Stability of thinned paint: To be used within 24 hours

Scrub Cycles: Sustains upto 15000 cycles

SAFETY FEATURES

- Kindly refer to the MSDS for JK Primera Interior Wall Primer which gives detailed information on safety measures while handling the primer.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink, etc.
- May be harmful, if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- Safety Data Sheet available for professional user on request.
- No added Lead, Mercury or Chromium compounds.