



JK ENAMELO

Premium Satin Enamel

JK ENAMELO PREMIUM SATIN ENAMEL is a highly durable enamel that offers a luxurious satin finish and stain resistance. Specially formulated to create a tough durable film, it ensures superior adhesion and long-lasting protection for metal, wood, and plaster surfaces. With excellent washability and backed by a 3-year warranty, it delivers enduring beauty and performance for your spaces.

PRODUCT BENEFITS/FEATURES



Rich Satin Finish



Tough Durable Film



Stain Resistant



3 Year Warranty*



Long Lasting



Excellent Brushability

AREAS OF APPLICATION

JK Enamelo Premium Satin Enamel can be applied on wood, metal, cement plaster, asbestos, and ceiling.

PACKAGING AVAILABLE



500 ML



1 L



4 L

COVERAGE

On normal masonry surface by brush/roller/spray



1 Coat 240-280 sq.ft/ltr

2 Coats 110-130 sq.ft/ltr

*Actual Coverage may vary from the quoted coverage due to factors such as method and condition of application, surface roughness and porosity.

COLORS AVAILABLE

Shades

Currently Available in 6 factory made shades and 2 bases as per the JK MaxX Paints Shade Card & Fandeck



FINISH

Satin

Smooth

HOW TO APPLY

NEW SURFACE PREPARATION

- Remove all grease, oil, dirt & glue using thinner.
- Remove rust and loosely bonded areas using sand paper or wire brush.

SAFETY PRECAUTIONS

- Store Enamelo Premium Satin Enamel in a cool and dry place.
- Keep the container tightly closed when not in use.
- Wash the brush/equipment with MTO/Thinner immediately after use.

SHELF LIFE

- 3 years from the date of manufacturing in the original tightly closed container, away from direct sunlight and excess heat.
- Lead contents does not exceed 90 ppm.
- No Added Mercury, Arsenic and Chromium.
- Stir well and strain before use.

ENAMELO APPLICATION PROCESS

APPLICATION	THINNER	DILUTION % VOLUME	APPLICATION VISCOSITY ¹ (by B4 Cup in seconds)	RECOATING PERIOD ² (HOURS)
Step 1 Sanding	Sand lightly with Sand paper 180 and wipe clean			
Step 2 First coat of JK Primera Red Oxide Metal Primer (Metal Surface)/ JK Primera White Primer ST (Wooden Surface)	MTO	5-10% for Brush 10-20% for Spray	5-10% for Brush 10-20% for Spray	4-6 Hrs (depending upon temperature & application)
Step 3	Remove Surface Imperfection with wall putty if any. Sand the surface with emery paper 220/320 and wipe clean.			
Step 4 Second Coat of JK Primera Red Oxide Metal Primer (Metal Surface)/ JK Primera White Primer ST (Wooden Surface)	MTO	5-10% for Brush 10-20% for Spray	5-10% for Brush 10-20% for Spray	4-6 Hrs (depending upon temperature & application)
Step 5 Second Coat of JK Enamelo Premium Satin Enamel Brush/Roller/Spray	MTO	5-10% for Brush 10-20% for Spray	40-60 Sec for Brush 20-25 Sec for Spray	NA

1. As measured through a Ford cup.

2. Recoating period is quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

3. Some shades may require 3 or more coats for proper hiding.

PRECAUTIONS

- Flammable, keep away from heat & flame.
- Close the container properly tightly closed after use.
- During application, keep the area properly ventilated.
- Addition of stainers or tinters, require thorough shaking immediately after & before painting.

TECHNICAL DETAILS

Surface Drying time: 3 hrs at ambient temperature

Flash point IS101/1987 Part 1, Sec 6: 35°C (95°F)

Sheen Levels: 15-35GU @60°GH on glass plate

Stability of thinned paint: Over night

SAFETY FEATURES

- Kindly refer to the MSDS for Enamelo Synthetic Enamel which gives detailed information on safety measures while handling the paint.
- Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses.
- In the event of spills, contain spillage using sand or earth.
- Safety Data Sheet available for professional user on request.
- No added Lead, Mercury or Chromium compounds.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place.
- Keep out of reach of children and away from food, drink etc.
- May be harmful, if swallowed. In case of ingestion, seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

*T&C apply. Please refer to the warranty documents for the product at the JK Maxx Paints Website for further information.